

AC118 Series

High G Measurement Accelerometer, Side Exit 2 Pin Connector, 50 mV/g, $\pm 10\%$



VIBRATION ANALYSIS HARDWARE



Product Features


50 mV/g General Purpose Side Exit Sensor

Excellent for Higher g Applications

- ▶ ± 100 g, Dynamic Range
- ▶ 50 mV/g, $\pm 10\%$ Sensitivity
- ▶ 1,0-10000 Hz (60-600,000 CPM)

AC118-1A 2 Pin Connector


Connector Pin	Polarity
A	(+) Signal/Power
B	(-) Common



Stock Product

AC118-2C CB103 Integral Cable


Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire



Built To Order

AC118-3C CB206 Armored Integral Cable


Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire



Built To Order

AC118-6C CB611 Heavy Duty Armored Integral Cable

Conductor	Polarity
Red	(+) Signal/Power
Black	(-) Common
Shield	Cable Drain Wire



Built To Order

Specifications	Standard	Metric	Specifications	Standard	Metric
Part Number	AC118	M/AC118	Environmental		
Sensitivity ($\pm 10\%$)	50 mV/g		Temperature Range	-58 to 250°F	-50 to 121 °C
Frequency Response (± 3 dB)	60-600,000 CPM	1,0-10000 Hz	Maximum Shock Protection	5,000 g, peak	
Frequency Response ($\pm 10\%$)	240-360,000 CPM	4,0-6000 Hz	Electromagnetic Sensitivity	CE	
Dynamic Range	± 100 g, peak		Sealing	Welded, Hermetic	
Electrical			Submersible Depth	200 ft.	60 m
Settling Time	<2 Seconds		Physical		
Voltage Source (IEPE)	18-30 VDC		Sensing Element	PZT Ceramic	
Constant Current Excitation	2-10 mA		Sensing Structure	Shear Mode	
Spectral Noise @ 10 Hz	8 μ g/ $\sqrt$ Hz		Weight	5.1 oz	145 grams
Spectral Noise @ 100 Hz	2.5 μ g/ $\sqrt$ Hz		Case Material	316L Stainless Steel	
Spectral Noise @ 1000 Hz	1.7 μ g/ $\sqrt$ Hz		Mounting	1/4-28	
Output Impedance	<100 ohm		Connector (Non-Integral)	2 Pin MIL-C-5015	
Bias Output Voltage	10-14 VDC		Resonant Frequency	1,260,000 CPM	21000 Hz
Case Isolation	>10 ⁸ ohm		Mounting Torque	2 to 5 ft. lbs.	2,7 to 6,8 Nm
			Mounting Hardware	1/4-28 Captive Bolt	M6x1 Captive Bolt